

Material Safety Data Sheet

CALCIUM CHLORIDE SOLUTION *DM35*



CAS NUMBER:

A. GENERAL INFORMATION

TRADE NAME (COMMON NAME):

CHEMICAL NAME AND/OR SYNONYM:

MOLECULE WEIGHT: LIQUID CALCIUM CHLORIDE, MAGNESIUM CHLORIDE, SODIUM CHLORIDE BRINE SOLUTION 110.98, 95.218, 58.453

10043-52-4 (anhydrous), 7647-14-5 (anhydrous), 7791-18-6

FORMULA:

DM 35

CaCl2, 27-30%, MgCl2. 4-7%, NaCl. Less than 2%,

MANUFACTURER/ADDRESS:

TRILLIUM DISTRIBUTION INC 2351 GREENFIELD RD COURTRIGHT, ONTARIO

N0N 1H0

PHONE NUMBER: CONTACT: **KEVIN POLLARD**

1-800-265-5619

LAST ISSUE DATE: January 31, 2017

CURRENT ISSUE DATE:

November 15.2017

B. FIRST AID MEASURES

EYES: Flush promptly with plenty of water, continuing for at least 15 minutes. Get medical attention.

SKIN: Wash with plenty of water.

INHALATION: Remove to fresh air.

INGESTION: If conscious, immediately give 2 to 4 glasses of water, and induce vomiting by touching finger to

back of throat.

Get medical attention for irritation, ingestion, or discomfort from inhalation.

EMERGENCY PHONE NUMBER:

(519)-796-8114

C. HAZARDS INFORMATION

Vapors are unlikely due to physical properties. Mists may cause irritation to the upper respiratory tract.

INGESTION:

If swallowed and the person is conscious, immediately give large amounts of water. Get medical attention.

SKIN: In case of contact, immediately wash skin with plenty of soap and water for at least 15 minutes						
C. HAZARDS (Cont.)						
EYES: In case of eye contact, immediately flush with ple	enty of water for at least 15 minutes.					
PERMISSIBLE CONCENTRATION: AIR NA		BIOLOGICAL: None				
UNUSUAL CHRONIC TOXICITY: None						
FLASH POINT:	AUTO IGNITION	FLAMMABLE LIMIT	S IN AIR (% BY VOL.)			
Not flammable	TEMPERATURE					
OPEN CUP ☐ CLOSED CUP ☐	NA	LOWER – NA	UPPER - NA			
UNUSUAL FIRE AND EXPLOSION HAZARDS NA						
D. PRECAUTIONS/PROCEDURES						
FIRE EXTINGUISHING AGENTS RECOMMENDED: Use extinguishing media appropriate for surrounding fire.						
FIRE EXTINGUISHING AGENTS TO AVOID:						
None identified						
SPECIAL FIREFIGHTING PRECAUTIONS: None identified						
VENTILATION: None identified						
NORMAL HANDLING: Avoid contact with eyes, skin or clothing. Use good personal hygiene and housekeeping.						
STORAGE: Keep container tightly closed. Suitable for any general chemical storage area.						
SPILL OR LEAK:						
Wear suitable protective clothing. Carefully sweep up and remove.						
SPECIAL: PRECAUTIONS/PROCEDURES/LABEL INSTRUCTIONS: None						
E. PERSONAL PROTECTIVE EQUIPMENT						
RESPIRATORY PROTECTION: None required where adequate ventilation conditions exist. If airborne concentration is high, use an appropriate respirator or dust mask.						
EYES AND FACE: Safety goggles						
HANDS, ARMS, AND BODY: Proper gloves are recommended						

F. PHYSICAL DATA				
MATERIAL IS AT NORMAL CONDITIONS:		APPEARAI	NCE AND COLOR:	
LIQUID SOLID GAS			Clear to slightly turbid liquid	
☐ Slurry		Oldar to slig	ntly tarbia liquia	
BOILING POINT: 116 °C APPROX	SPECIFIC GI		VAPOR DENSITY:	
MELTING POINT: 7 °C APPROX	(H ₂ O = 1)	1.30 TO 1.37	(AIR =1) Not applicable	
SOLUBILITY IN WATER:	pH		VAPOR PRESSURE:	
% BY WEIGHT Very Soluble as CaCl2, 45%, NaCl, 24%, MgCl2, 35%	slightly ac	cidic	(mm Hg @ 20°C) ☐ (PSIG) ☐ mm Hg @ 20 C 1.1 kPa 35%	
EVAPORATION RATE:		S BY VOLUME:		
(Butyl acetate =1) ☐ (Ether = 1.0) ☐ ((AT 20°C) Not applicable		
Not applicable				
S. REACTIVITY DATA				
nenomin shin				
STABILITY:	CONDITIONS TO A	/OID:		
	CONDITIONS TO AN Not applicable	/OID:		
INSTABLE ☐ STABLE ⊠		/OID:		
NCOMPATIBILITY (MATERIALS TO AVOID): Reacts violently with bromine trifluoride (BrF3), or a mixture of	Not applicable of boron trioxide and calciu	m oxide (B2O3 + CaO).	Water-reactive materials, such as sodium;	
NCOMPATIBILITY (MATERIALS TO AVOID): Reacts violently with bromine trifluoride (BrF3), or a mixture of traces an exothermic reaction. Methyl vinyl ether; starts rui	Not applicable of boron trioxide and calciu	m oxide (B2O3 + CaO).	Water-reactive materials, such as sodium; yields hydrogen gas, which may explode	
NCOMPATIBILITY (MATERIALS TO AVOID): Reacts violently with bromine trifluoride (BrF3), or a mixture of the sauses an exothermic reaction. Methyl vinyl ether; starts run explode under these conditions. HAZARDOUS DECOMPOSITION PRODUCTS:	Not applicable of boron trioxide and calciunaway polymerzation. Zin	m oxide (B2O3 + CaO).	Water-reactive materials, such as sodium; yields hydrogen gas, which may explode	
NCOMPATIBILITY (MATERIALS TO AVOID): Reacts violently with bromine trifluoride (BrF3), or a mixture of trigonal control of the	Not applicable of boron trioxide and calciunaway polymerzation. Zin	m oxide (B2O3 + CaO).	Water-reactive materials, such as sodium; yields hydrogen gas, which may explode	
NCOMPATIBILITY (MATERIALS TO AVOID): Reacts violently with bromine trifluoride (BrF3), or a mixture of causes an exothermic reaction. Methyl vinyl ether; starts run explode under these conditions. HAZARDOUS DECOMPOSITION PRODUCTS: Fumes of Chlorides (CI-) are given off at temperatures above	Not applicable of boron trioxide and calciunaway polymerzation. Zin	m oxide (B2O3 + CaO). c as in galvanized iron;	yields hydrogen gas, which may explode	
NCOMPATIBILITY (MATERIALS TO AVOID): Reacts violently with bromine trifluoride (BrF3), or a mixture of causes an exothermic reaction. Methyl vinyl ether; starts run explode under these conditions. HAZARDOUS DECOMPOSITION PRODUCTS: Fumes of Chlorides (CI-) are given off at temperatures above HAZARDOUS POLYMERIZATION:	Not applicable of boron trioxide and calciunaway polymerzation. Zin	m oxide (B2O3 + CaO). c as in galvanized iron; OTHER PRE Will undergo The anhydro	yields hydrogen gas, which may explode CAUTIONS: o violent polymerization with methyl vinyl ether. us, monohydrate, dihydrate and tetrahydrate	
NCOMPATIBILITY (MATERIALS TO AVOID): Reacts violently with bromine trifluoride (BrF3), or a mixture of causes an exothermic reaction. Methyl vinyl ether; starts run explode under these conditions. HAZARDOUS DECOMPOSITION PRODUCTS: Fumes of Chlorides (CI-) are given off at temperatures above	Not applicable of boron trioxide and calciunaway polymerzation. Zin	m oxide (B2O3 + CaO). c as in galvanized iron; OTHER PRE Will undergo The anhydro forms of calc	yields hydrogen gas, which may explode CAUTIONS: o violent polymerization with methyl vinyl ether. us, monohydrate, dihydrate and tetrahydrate	
NCOMPATIBILITY (MATERIALS TO AVOID): Reacts violently with bromine trifluoride (BrF3), or a mixture of causes an exothermic reaction. Methyl vinyl ether; starts run explode under these conditions. HAZARDOUS DECOMPOSITION PRODUCTS: Fumes of Chlorides (CI-) are given off at temperatures above HAZARDOUS POLYMERIZATION: WILL NOT OCCUR	Not applicable of boron trioxide and calciunaway polymerzation. Zin	m oxide (B2O3 + CaO). c as in galvanized iron; OTHER PRE Will undergo The anhydro forms of calc	cautions: o violent polymerization with methyl vinyl ether. us, monohydrate, dihydrate and tetrahydrate ium chloride, when dissolved in water, produce	
NCOMPATIBILITY (MATERIALS TO AVOID): Reacts violently with bromine trifluoride (BrF3), or a mixture of causes an exothermic reaction. Methyl vinyl ether; starts run explode under these conditions. HAZARDOUS DECOMPOSITION PRODUCTS: Fumes of Chlorides (CI-) are given off at temperatures above HAZARDOUS POLYMERIZATION: WILL NOT OCCUR	Not applicable of boron trioxide and calciunaway polymerzation. Zin	m oxide (B2O3 + CaO). c as in galvanized iron; OTHER PRE Will undergo The anhydro forms of calc	cautions: o violent polymerization with methyl vinyl ether. us, monohydrate, dihydrate and tetrahydrate ium chloride, when dissolved in water, produce	
NCOMPATIBILITY (MATERIALS TO AVOID): Reacts violently with bromine trifluoride (BrF3), or a mixture of causes an exothermic reaction. Methyl vinyl ether; starts run explode under these conditions. HAZARDOUS DECOMPOSITION PRODUCTS: Fumes of Chlorides (CI-) are given off at temperatures above HAZARDOUS POLYMERIZATION: WILL NOT OCCUR MAY OCCUR	Not applicable of boron trioxide and calciunaway polymerzation. Zin	m oxide (B2O3 + CaO). c as in galvanized iron; OTHER PRE Will undergo The anhydro forms of calc	cautions: o violent polymerization with methyl vinyl ether. us, monohydrate, dihydrate and tetrahydrate ium chloride, when dissolved in water, produce	

Not applicable				
I. ENVIRONMENTAL				
I. ENVIRONMENTAL				
DEGRADABILITY/AQUATIC TOXICITY:		OCTANOL/WATER PARTITION		
Harmful to aquatic life at concentrations greater than 500 ppm. CaCl2 , NaCl a	COEFFICIENT			
Does not bioaccumulate. TLm 96>100mg/1		NA		
Aquatic Toxicity: None identified	L			
Aquatio Toxiony. None identified				
EPA HAZARDOUS SUBSTANCE?	007401 5 0114NTTV			
(CLEAN WATER ACT SECT. 311) YES NO IF SO, REP WASTE DISPOSAL METHODS (DISPOSER MUST COMPLY WITH FEDERAL,	ORTABLE QUANTITY:	CAL OR DISCHARGE LAWS).		
WASTE DISPOSAL METHODS (DISPOSER MOST COMPLY WITH FEDERAL,	STATE AND LOCAL DISPO	SAL OR DISCHARGE LAWS).		
Treatment or disposal of waste generated by use of this product should be review	ved in terms of applicable fede	ral, state and local laws and regulations.		
Users are advised to consult with appropriate regulatory agencies before discharge	ge, treatment or disposal.	_		
RCRA STATUS OF <u>UNUSED</u> MATERIAL IF DISCARDED:	HAZARDOUS WASTE NUM	/IBER: (IF APPLICABLE)		
Not a "hazardous waste".	-			
J. REFERENCES				
PERMISSIBLE CONCENTRATIONS REFERENCES:				
None				
REGULATORY STANDARDS:		DOT CLASSIFICATION:		
		Not regulated		
None				
GENERAL:				
K. ADDITIONAL INFORMATION				
	<u> </u>			

THIS MATERIAL SAFETY DATA SHEET IS OFFERED SOLELY FOR YOUR INFORMATION. CONSIDERATION AND INVESTIGATION.

TRILLIUM DISTRIBUTION PROVIDES NO WARRANTIES, EITHER EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA CONTAINED HEREIN. THIS DOCUMENT IS INTENDED ONLY AS A GUIDE TO THE APPROPRIATE PRECAUTIONARY HANDLING OF THE MATERIAL BY A PROPERLY TRAINED PERSON USING THIS PRODUCT. INDIVIDUALS RECEIVING THE INFORMATION MUST EXERCISE THEIR INDEPENDENT JUDGEMENT IN DETERMINING ITS APPROPRIATENESS FOR A PARTICULAR PURPOSE.